

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>6</sup> : <b>B65D 83/16</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 99/33716</b> (43) International Publication Date: <b>8 July 1999 (08.07.99)</b></p>
<p>(21) International Application Number: <b>PCT/EP98/08151</b> (22) International Filing Date: <b>10 December 1998 (10.12.98)</b> (30) Priority Data: <b>9727366.8</b>      <b>24 December 1997 (24.12.97)</b>      <b>GB</b> (71) Applicants: <b>UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB). UNILEVER NV [NL/NL]; Weena 455, 3013 AL Rotterdam (NL).</b> (71) Applicant (for IN only): <b>HINDUSTAN LEVER LIMITED [IN/IN]; Hindustan Lever House, 165/166 Backbay Reclamation, Mumbai, 400 020 Maharashtra (IN).</b> (72) Inventors: <b>CLARK, Norman; Elida Faberge Ltd., Coal Road, Seacroft, Leeds LS14 2AR (GB). MIDGLEY, Ian; Elida Faberge Ltd., Coal Road, Seacroft, Leeds LS14 2AR (GB).</b> (74) Agent: <b>PEARCE, Timothy; Unilever plc, Patent Dept., Colworth House, Sharnbrook, Bedford MK44 1LQ (GB).</b></p>		<p>(81) Designated States: <b>AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</b>  <b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>

(54) Title: **SPRAYHEAD**

(57) Abstract

A sprayhead (1) for example for an aerosol or pumpspray container (4) comprises a support (2), a fluid outlet (12) mounted on the support (2), a passageway (14) connected to the fluid outlet (12) at a first end and connectable to a fluid source at a second end, the passageway (14) being movable between a first non-operative position and a second position in which, in use, it is connected to a fluid source such that fluid can pass through the passageway to the fluid outlet, a member (3) secured relative to the support (2), the member being movable between a non-operative position and a further position in which it allows the passageway (14) to attain its second position, and a lock (28) selectively operable to lock the member in its first position, thereby preventing the member from urging the passageway to its second position unless the lock is released.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

SPRAYHEAD

The invention relates to a sprayhead, and particularly,  
though not exclusively to a sprayhead for use with aerosol  
5 or pumpspray containers.

Aerosol containers contain fluid under pressure and a  
sprayhead is attached to the top of the container.  
Similarly, pumpspray containers typically contain fluid  
10 which is not pressurised, but which can be dispensed with  
the aid of a suitable pumpspray mechanism via a sprayhead.  
In both cases, when the sprayhead is depressed, the fluid in  
the container is forced out through an outlet in the  
sprayhead and the fluid spray is released. However, known  
15 sprayheads for use on either type of spray container are  
vulnerable to accidental operation, and it is normally  
necessary for a lid to be provided to prevent accidental  
release of the fluid.

20 An alternative means of prevent accidental release of fluid  
aerosol containers is disclosed in GB 1292843, US 5388730,  
US4418842, US3860149, and US 3848778. In those  
specifications, the sprayhead is rotatable about the supply  
line from the fluid reservoir within the container. In one  
25 position, the sprayhead can be depressed to enable the  
contents to be discharged, but after rotation around the  
axis of the supply line, depression of the sprayhead is  
physically obstructed, thereby preventing discharge.  
Continued rotation of the sprayhead relative to the supply  
30 line at their interface causes wear and can result in  
leakage of the contents at the interface and impaired  
operation of the aerosol.

The invention provides a sprayhead comprising:  
35 a support;

- 2 -

a passageway, mounted on the support, connectable to a switchable source of fluid and incorporating a fluid outlet, the passageway being moveable between a first, non-operative position and a second position in which it switches the source to supply fluid to the outlet via the passageway;

5 a member secured relative to the support, the member being moveable between a first non-operative position when the member is supported by a cam means on the support, and a further position in which the passageway may switch the source to supply fluid; and

10 a lock selectively operable to lock the member in its first position, thereby preventing the member from urging the passageway to its second position unless the lock is released.

15 Preferably, when the member secured relative to the support is in the further position at which the fluid may be supplied, when activated the member depresses to actuate (in the case of a pressurised aerosol) a valve on the pressurised aerosol, thereby allowing fluid to pass through the passageway. In the case of a pumpspray, similar activation may cause actuation of the pumpspray mechanism to allow fluid to pass through the passageway.

20 Conveniently, the movement of the passageway is in a plane normal to longitudinal axis of a valve connector which may be located adjacent to, and in fluid connection with the passageway. The longitudinal axis of the valve connector may be coaxial with a radial axis of the sprayhead.

25 Conveniently, the movement of the member secured relative to the support may be rotational, about a radial axis of the sprayhead.

30 Preferably the fluid outlet is mounted on the support via a

- 3 -

living hinge which is resiliently biased to urge the passageway to its first non-operative position. Such a position may allow (in the case of attachment to a pressurised aerosol) the valve on the aerosol container to  
5 be closed when a depression force is removed from the member; hence it is biased in the non-depressed position.

Preferably the member is mounted on the support via a living hinge which is resiliently biased to urge the member to its  
10 non-operative (ie non-depressed) position.

Advantageously the member shields the passageway such that the fluid may only be expelled from the passageway by movement of the member to the operative position.

15

Preferably the support comprises a base and a top, the base being mountable on a fluid container and the top being mounted on the base. Advantageously the member is integrally formed with the top of the support.

20 Alternatively to a base and a top, the support can comprise a base and a collar, the base being mountable on a fluid container and the collar being mounted around the base. In such supports, the member is advantageously integrally formed with the base above the passageway.

25

Advantageously, the lock comprises complementary cam means on the base and the top or collar such that movement of the top or collar relative to the base moves the corresponding cam means relative to one another between a first position  
30 in which the member is retained in its inoperative position and a second position in which the member can be moved to urge the passageway to its second (operative, dispensing) position.

35 Advantageously the top or collar is rotatable relative to

- 4 -

the base. Especially desirably, the base and particularly the passageway is not rotatable axially relative to a fluid supply means from the fluid reservoir, such as the stem outlet from the supply valve, thereby avoiding wear at an interface between the fluid passageway in the sprayhead and the stem outlet which could arise if the passageway were able to rotate axially around the stem outlet.

Preferably the cam means comprises one of a cam profile and a cam follower on the base and the other of a cam profile or cam follower on the top or collar. Advantageously the cam means on the base comprises a cam profile and the cam means on the top comprises a cam follower on the member or cam means on the collar comprises a cam follower.

Preferably the base comprises plastics material and is moulded in one piece. Preferably the top comprises plastics material and is moulded in one piece. Preferably the collar is moulded in one piece. Advantageously the top or collar and base comprise co-operating fastening means that snap fit together.

Preferably the top comprises a body portion and the member comprises a cut-away portion linked to the body portion by a flexible hinge.

Advantageously the member comprises catch means to prevent raising of the member with respect to the body portion of the top.

Advantageously the top comprises an opening in the body portion for co-operation with the fluid outlet.

Advantageously, the base diameter is larger than the top diameter, to allow the sprayhead to be placed efficiently

- 5 -

onto the container.

When a collar is employed instead of a top, the base preferably comprises a body portion attached to the member, and the collar preferably comprises an opening for cooperation with the fluid outlet.

Advantageously, one of the base and top or collar further comprises an indentation in its external face extending away from the boundary between the base and top or collar, and the other of the base and top or collar further comprises a tongue which fits the indentation, thereby preventing rotation of the top or collar relative to the base when the tongue is in place within the indentation. The tongue is desirable hinged such that it can be lifted out of the indentation, and preferably, the tongue is moulded in one piece with the respective top or bottom.. The tongue and indentation and are preferably disposed relative to each other around their respective circumferences such that when they are in alignment, the member is locked in its first position, ie preventing the member from urging the passageway to its second position and the fluid outlet is covered by the top. Particularly, the tongue extends downwardly from the top and the base carries the indentation.

It is an advantage of the present invention that it provides a sprayhead for an aerosol, pumpspray or similar container that can be moved between an operable and an inoperable state.

The invention also resides in a container, especially an aerosol or pumpspray fluid container, including a spray head as defined hereinabove.

35

- 6 -

The invention will now be described, by way of example only, with reference to the accompanying drawings, of which:

Figure 1 shows a side view of a sprayhead according to the invention mounted on a fluid container;

Figure 2 shows the base of the sprayhead shown in Figure 1 in cross section;

Figure 3 shows the base of the sprayhead in plan view;

Figure 4 shows the top of the sprayhead shown in Figure 1 in cross section; and

Figure 5 shows the top of the sprayhead in plan view.

Figure 6 shows a further side view of the spray head mounted on a fluid container

As shown in Figure 1, a sprayhead 1 of the invention comprises a base 2 and a top 3 fixedly mounted on the base 2. The sprayhead 1 is shown mounted on an aerosol container 4, this being the normal manner of use of the sprayhead.

20

Referring also to Figures 2 and 3, the base 2 comprises a skirt portion 5 which includes moulded snap-fit segments 6 for connectably mounting the base 2 onto a neck 7 of the container 4. The container has protruding (but not shown) a stem piece through which fluid contained in the aerosol container may be released.

A plate section 8 is formed at the top of the skirt portion 5 and snap-fit segments 9 are formed integrally with the plate section 8 for fastening the base 2 to the top 3. An outlet closure plate 10 and a cam profile 11 are also formed on the plate section 8.

A fluid outlet 12 is formed in a plate 13 extending upwards from the skirt portion 5. A passageway 14 extends from the



- 7 -

fluid outlet 12 to a valve connector 15 arranged centrally in the base 2 for fluid engagement via the stem piece with a valve connected to a pipe extending into fluid in the aerosol can (not shown). The valve connector 15 and  
5 passageway 14 can be depressed downwardly and are of sufficient resilience to return to a rest position when the depressing force is removed.

Referring now to Figures 4 and 5, the top 3 comprises a  
10 single integral moulding comprising a body portion 16 and a depressor member 17 connected to the body portion 16 by an integral flexible hinge portion 18. The depressor member 17 has a finger pad 19 sized for comfortable fit with a user's finger (not shown) and having ridges 20 to reduce the  
15 likelihood of a user's finger slipping during use of the sprayhead 1. The top 3 further includes snap-fit segments 21 for co-operation with the snap-fit segments 9 of the base 2 and a cam follower 22 for co-operation with the cam profile 11 formed on the base 2. A protuberance 23  
20 restricts the depressor member 17 from being raised above the body portion 16 and an opening 24 corresponds to the fluid outlet 12.

Referring now to Figure 6, the base 2 is cut away to provide  
25 an indentation 29 in which sits a fitting tongue 28 extending down from and moulded with top 3. Tongue 28 is joined with top 3 at hinge 30. The opening 24 is not aligned with fluid outlet 12, so that it cannot be seen in this figure.

30 In use, the top 3 is snap-fitted to the base 2 and the complete sprayhead 1 is mounted on an aerosol container 4. Tongue 28 is pivoted about hinge 30 and lifted out of indentation 29. The depressor member 17 is pressed down by  
35 a user's finger, pushing the valve connector 15 down to

- 8 -

contact the valve (not shown) in the aerosol container 4 and allow fluid to flow through the passageway 14 and out of the fluid outlet 12 as a spray. When the depressor member 17 is released, the depressor member 17 returns to its rest  
5 position and the valve connector 15 and passageway 14 return to their rest position, thus shutting off the flow of fluid.

To prevent inadvertent activation of the sprayhead 1, the top 3 can be rotated relative to the base 2 around the snap  
10 fittings 9 on the plate 8. As the top 3 is rotated, the cam follower 22 moves to a position over and then along the cam profile 11. The cam follower 22 is held in a raised position by the cam profile 11 and prevents depression of the depressor means 17 and thus prevents activation of the  
15 sprayhead 1. This position is releasably retained by the action of locking ribs 25 interfering with snap-fittings 26 on the base 2.

As the top 3 is rotated, the opening 24 moves around with  
20 the top 3 until, in the completely closed position, the opening 24 corresponds to the outlet closure plate 10 and the fluid outlet 12 faces a section of the body portion 16 for complete closure of the fluid outlet 12. In this position, the sprayhead 1 is completely closed and cannot be  
25 activated inadvertently. The position is retained by the action of locking ribs 25 interfering with the snap fittings 27 on the base 2.

To open the sprayhead 1 for use, the top 3 is rotated in a  
30 reverse direction relative to the base 2 and the cam follower 22 moves along the cam profile 11 to a position in which the depressor means 17 can be depressed and the sprayhead 1 can be activated.

35 The invention provides a simple and easily operated

- 9 -

self-closing sprayhead for aerosols and similar that can be used without having to have a separate lid or closure means provided.

- 10 -

**CLAIMS**

1. A sprayhead comprising:  
a support;  
a passageway, mounted on the support, connectable to a switchable source of fluid and incorporating a fluid outlet, the passageway being moveable between a first, non-operative position and a second position in which it switches the source to supply fluid to the outlet via the passageway;  
a member secured relative to the support, the member being moveable between a first non-operative position when the member is supported by a cam means on the support, and a further position in which the passageway may switch the source to supply fluid; and  
a lock selectively operable to lock the member in its first position, thereby preventing the member from urging the passageway to its second position unless the lock is released.
2. A sprayhead according to claim 1 wherein the fluid outlet is mounted on the support via a living hinge which is resiliently biased to urge the passageway to its first non-operative position.
3. A sprayhead according to claim 1 or claim 2 wherein the member is mounted on the support via a living hinge which is resiliently biased to urge the member to its non-operative position.
4. A sprayhead according to any one of the preceding claims wherein the member shields the passageway such that the passageway may only be movable to its second position by movement of the member.

- 11 -

5. A sprayhead according to any one of the preceding claims wherein the support comprises a base and a top, the base being mountable on a fluid container and the top being mounted on the base.
6. A sprayhead according to claim 5 wherein the member is integrally formed with the top of the support.
7. A sprayhead according to any of claims 1 to 4 wherein the support comprises a base and a collar, the base being mountable on a fluid container and the collar being mounted around the base.
8. A sprayhead according to any one of claims 5 to 7 wherein the lock comprises complementary cam means on the base and the top or collar such that movement of respectively the top or collar relative to the base moves the corresponding cam means relative to one another between a first position in which the member is retained in its inoperative position and a second position in which the member can be moved to urge the passageway to its second position.
9. A sprayhead according to any one of claims 5 to 8 wherein the cam means comprises one of a cam profile and a cam follower on the base and the other of a cam profile or cam follower on respectively the top or collar.
10. A sprayhead according to claim 9 wherein the cam means on the base comprises a cam profile and the cam means on the top comprises a cam follower on the member.
11. A sprayhead according to any one of claims 5, 6, or 8 to 10 wherein the top is rotatable relative to the

- 12 -

base.

12. A sprayhead according to any one of claims 7 to 10 wherein the collar is rotatable relative to the base.
13. A sprayhead according to claim 11 wherein one of the top and base further comprises a tongue and the other of the top and base comprises a matching indentation, preventing relative rotation of the top and base when the tongue is located within the indentation.
14. A sprayhead according to claim 12 wherein one of the collar and base further comprises a tongue and the other of the collar and base comprises a matching indentation, preventing relative rotation of the collar and base when the tongue is located within the indentation.
15. A sprayhead according to any one of claims 5 to 14 wherein the base comprises plastics material and is moulded in one piece.
16. A sprayhead according to any one of claims 5, 6, 8 to 11, 13 or 15 wherein the top comprises plastics material and is moulded in one piece.
17. A sprayhead according to any one of claims 7 to 10, 14 or 15 wherein the collar comprises plastics material and is moulded in one piece.
18. A sprayhead according to any one of claims 5, 6, 8 to 11, 13 15 or 16 wherein the top and base comprise co-operating fastening means that snap fit together.
19. A sprayhead according to any one of claims 5, 6, 8 to

- 13 -

- 11, 13 15 to 18 wherein the top comprises a body portion and the member comprises a cut-away portion linked to the body portion by a flexible hinge.
20. A sprayhead according to any one of claims 5, 6, 8 to 11, 13, or 15 to 19 wherein the top comprises an opening in the body portion for co-operation with the fluid outlet.
21. A sprayhead according to any one of claims 5 to 20 wherein the member comprises catch means to prevent raising of the member with respect to the body portion of the top or the collar.
22. A sprayhead according to any preceding claim wherein the base is non-rotatable axially relative to a fluid supply line from a fluid reservoir.
23. An aerosol container comprising a sprayhead according to any one of the preceding claims.
24. A pumpspray container comprising a sprayhead according to any one of the preceding claims.
25. A sprayhead as hereinbefore described with reference to the accompanying drawings.

1/2




Fig.2.




Fig.3.






Fig.4.




Fig.5.





Fig.6.



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 98/08151

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 B65D83/16

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 409 497 A (TIRAM KIMIA SDN BHD) 23 January 1991  see the whole document ---	1-6, 8-11, 15, 16, 18, 22, 23
Y	US 3 848 778 A (MESHBERG P) 19 November 1974 cited in the application  see column 2, line 10 - line 18; figure 18 ---	1-6, 8-11, 15, 16, 18, 22, 23
A	EP 0 119 084 A (METAL BOX PLC) 19 September 1984  see the whole document ---  -/--	1-5, 9-11, 15, 16, 18, 19, 21-23

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

6 May 1999

Date of mailing of the international search report

17/05/1999

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Béraud, F

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 98/08151

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>EP 0 503 735 A (PLASTICUM NV)  16 September 1992  see figures 1,2  -----</p>	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 98/08151

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0409497	A	23-01-1991	AU 638259 B AU 5807290 A CA 2020223 A,C US 5158206 A	24-06-1993 24-01-1991 20-01-1991 27-10-1992
US 3848778	A	19-11-1974	NONE	
EP 0119084	A	19-09-1984	DK 110684 A GB 2136507 A,B GR 81873 A US 4542837 A ZA 8401493 A	13-09-1984 19-09-1984 12-12-1984 24-09-1985 30-10-1985
EP 0503735	A	16-09-1992	NL 9100406 A AT 154792 T DE 69220521 D US 5242087 A	01-10-1992 15-07-1997 31-07-1997 07-09-1993